


Bicycle Technical Guidelines



A Guide for Local Agencies in Santa Clara County

1. R_h - Radius of horizontal curve per site conditions (no bike/ped conflicts with motor vehicles)
2. R_c = Curb radius at ramp terminal intersections to be 20-25 feet maximum for optimum ped bike accommodation.
3. Posted speed limit on Arterial 35 mph maximum.




Bicycle Technical Guidelines

A Guide for Local Agencies in the Planning, Design and Maintenance of Bicycle Facilities and Bicycle-Friendly Roadways

Prepared by the
Santa Clara Valley Transportation Authority
Adopted September 2, 1999
Revision 1 adopted December 13, 2007
Revision 2 adopted December 13, 2012
Revision 3 adopted March 3, 2022

HOW TO OBTAIN THE CURRENT VTA BICYCLE TECHNICAL GUIDELINES (BTG)

The current version of the BTG is available on the VTA website at http://www.vta.org/bike_information/bicycle_technical_guidelines.html. Pages are updated individually as the need arises; individual pages should be downloaded by holders of this manual as needed. Sign up to receive an email notice of future revisions by going to http://www.vta.org/bike_information/bicycle_technical_guidelines.html and clicking on this icon: 

Revisions to the Board-adopted version of the December 2007 BTG are itemized below.

Date Effective	Page or Section	Topic
10/02/08	App. A-4	Caltrans DD 64-R1 replaced DD64
Dec 2012	i- x	New table of contents to reflect changes below
Dec 2012	Chapters 1, 3, 5, 7, 9	Entire chapters revised and new information added on (e.g Ch 3 Bus rapid transit, Ch. 7.5 Cycle Tracks, Ch 9.4 Bollards.)
Dec. 2012	2-1, 4-1, 6-1, 6-5, 6-8, 8-1, 8-8	Minor updates to cross reference new sections and to reflect updated MUTCD and State Laws
Dec. 2012	Section 8.4	New section 8.4 on woonerfs
Dec 2012	Appendix C	New appendix on bridge railings
Mar 2022	Chapter 10	Entire chapter revised and new information added on bicycle storage rooms and micromobility parking; updated graphics and table showing the recommended number of bicycle spaces by land use type

Form

As in the Highway Design Manual (HDM), the loose-leaf form was chosen for the BTG because it facilitates change and expansion. New guidelines will be issued as pages in the format of this manual; these may consist of additional pages or new pages to be substituted for those superseded, as listed in the Table above.

Reproduction

This document may be reprinted whole or in part from the VTA website cited above for the sole use and purpose of conducting bike-friendly planning and design. If any part of this document is reproduced for this purpose, cite VTA Bicycle Technical Guidelines and the date as the source. No part of this work may be used or reproduced in any form, electronic, graphic, or mechanical, for marketing or other commercial purpose of any public or private agency or entity or for any reason other than that cited above.

This page intentionally left blank for duplex printing

Bicycle Technical Guidelines

Table of Contents

Part I – General Guidance

Chapter 1 Purpose and Policy Guidance

1.1	Organization of Manual	1-1
1.2	Who Uses These Guidelines?.....	1-4
1.3	Relation to Other Design Manuals.....	1-4
1.4	Consistency with Existing Policies.....	1-6

Chapter 2 Bicycle Characteristics

2.1	Defining Optimum, Should and Shall.....	2-1
2.2	Bicycle User Types	2-1
2.3	Facility Types and Bicycle Users.....	2-2
2.4	Operating Space of a Typical Bicyclist	2-3

Part II – Technical Guidelines for All Roadways

Chapter 3 Roadway Design Elements

3.1	Roadway and Lane Width.....	3-1
3.2	Drainage Inlets and Gutter Pans	3-4
3.3	Pavement Marking Materials.....	3-6
3.4	Roadway Surface Obstacles	3-7
3.5	Signage Usage and Design	3-10
3.6	Bulbout Design	3-14

Chapter 4 Maintenance and Construction Zones

4.1	Roadway Resurfacing.....	4-1
4.2	Roadway Patching and Utility Trenching Repair.....	4-2
4.3	Ponding.....	4-3
4.4	Sweeping.....	4-3
4.5	Landscape Maintenance.....	4-3
4.6	Construction Zones and Detours.....	4-4

Chapter 5 Intersections and Interchanges

5.1	Right Turns and Right-Turn Only Lanes	5-1
5.2	Left Turns and Left-Turn Only Lanes.....	5-11
5.3	Freeway Interchanges	5-13
5.4	Highway Grade-Separated Interchanges	5-25

Chapter 6 Signalized Intersections

6.1 Traffic Signal Timing 6-1
 6.2 Traffic Signal Detection 6-5
 6.3 Bicycle Signal Heads..... 6-8

Part III – Technical Guidelines For Bikeways On Roadways

Chapter 7 Bikeways on Major and Rural Roads

7.1 Bike Lanes 7-2
 7.2 Wide Curb Lanes 7-18
 7.3 Shared Roadway Bicycle Marking (Sharrow)..... 7-19
 7.4 Rural Roads and State Highways 7-21
 7.5 Cycle Tracks..... 7-31

Chapter 8 Local Roads as Bikeways

8.1 Bike Routes and Signed Shared Roadways..... 8-2
 8.2 Bike Boulevards..... 8-4
 8.3 Bicycle-FriendlyTraffic Calming 8-7
 8.4 Woonerfs A.K.A. Shared Spaces..... 8-9

Part IV – Technical Guidelines For Bike-Only Facilities

Chapter 9 Bike Paths and Bike Bridges

9.1 Bike Paths and Transportation Issues 9-1
 9.2 Trail/Roadway Intersections 9-8
 9.3 Bicycle/Pedestrian Across Barrier Connections 9-10
 9.4 Bollards & Preventing Motor Vehicle Access to Bike Paths 9-14
 9.5 Rural Roadside Paths..... 9-17
 9.6 Median Bike Paths..... 9-19

Chapter 10 Bike Parking

10.1 Definitions..... 10-1
 10.2 Class 1 Bike Parking Options 10-2
 10.3 Class 2 Bike Rack Options..... 10-6
 10.4 Placement Dimensions and Criteria 10-8
 10.5 Bike Parking Quantity 10-13
 10.6 Bike Parking Policies and Guidelines by Land Use Type..... 10-15

Chapter 11 Bicycle Accommodation Guidelines on County Expressways

Detailed Issue Discussion

Detour Evaluation Examples4-7

Signal Timing Example6-4

Potential Issues Related to 24-hour Access on Bike Paths9-4

Discussion on Railing Height9-13

Appendix A Bicycle Transportation Policies and Statues

1. California Vehicle Code Sections 21960 and 23330
2. California Streets and Highways Code Section 887-894
3. California Assembly Concurrent Resolution
4. Caltrans Deputy Directive 64-R1 Complete Streets, 10-2-08
5. Caltrans Director’s Policy Context Sensitive Solutions, 1-29-01

Appendix B MTC Resolution #3765 Routine Accommodation

Appendix C Roadway Bridge Rail and Barrier Options

Appendix D Bicycle Signal Head Warrants per MUTCD (CA)

Appendix E Trail Design Checklists

1. Trail Review Checklist from the *Contra Costa County Trail Review Study*
2. Figure 9-1 Ramp Design from the *Contra Costa County Trail Design Resource Handbook March 2001*

Appendix F Acronyms

Acknowledgements

List of Tables

Table 1-1:	Design Standards and Guidance Manuals for Streets and Bikeways.....	1-2
Table 2-1:	Bicyclist Type by Skill Level by Trip Purpose.....	2-1
Table 2-2:	Bicyclist Type Versus Facility Type.....	2-2
Table 3-1:	Optimum Bike Lane Widths.....	3-1
Table 3-2:	Railings on Roadway Bridges.....	3-3
Table 3-3:	Bikeway Surface Tolerances.....	3-7
Table 4-1:	Optimal Maintenance Frequencies for Roads and Trails	4-3
Table 4-2:	Bikeway Closure Evaluation Questions	4-5
Table 6-1:	Representative Bicyclist Speeds	6-1
Table 7-1:	Minimum Lane and Shoulder Widths for Two-Lane Rural Highways	7-21
Table 7-2:	Optimum Shoulder Widths Recommended by AASHTO	7-24
Table 7-3:	Differences Between a Side Path and a Cycle Track	7-31
Table 7-4:	Cycle Track Elements	7-32
Table 10-1:	Bike Locker Variations and Management Strategies	10-2
Table 10-2:	Bike Stations/Bike Rooms Management Strategies.....	10-5
Table 10-3:	Bicycle Parking Supply Recommendations.....	10-14

List of Figures

Figure 2-1:	Bicyclist Essential Operating Space	2-3
Figure 2-2:	Stationary Bicyclist with Trailer	2-3
Figure 2-3:	Bicyclist on Two-Way Path - Essential Operating Space	2-4
Figure 3-1:	Bikeway Crossing Skewed Railroad Tracks.....	3-8
Figure 3-2:	Rail Flangeway Filler Options.....	3-8
Figure 3-3:	Bulbout Design On Street Without Bike Lanes	3-15
Figure 3-4:	Bulbout Detail - Slope at Gutter Pan	3-16
Figure 4-1:	Wedge Cut for Roadway Resurfacing	4-1
Figure 4-2:	Trenching and Compacting Procedures.....	4-2
Figure 4-3:	Bike Detour Plan for Closed Street or Path.....	4-5
Figure 5-1:	Bike Lane Striping at Right-Turn Only Lane	5-3
Figure 5-2:	Dropped Bike lane at Right-Turn Only Lane - Option 3	5-5
Figure 5-3:	Dropped Bike lane at Right-Turn Only Lane - Option 4	5-5
Figure 5-4:	Bike Lane Striping of T-Intersection with Right-Turn and Left-Turn Lanes	5-6
Figure 5-5:	Right-Turn Channelization Island	5-7

Figure 5-6: Bike Lane at Free Right-Turn Lane.....5-8

Figure 5-7: Bicycle Accommodation Issues at Free Right-Turn Lanes5-9

Figure 5-8: Travel Path of Cyclist at Right-Turn Lane plus Optional Right-Turn Lane5-10

Figure 5-9: Left-Turn Options for Bicyclists5-11

Figure 5-10: Bike Lane Striping at Left-turn Only Lane5-12

Figure 5-11: Typical Local Street/Freeway Interchanges5-13

Figure 5-12: VTA Best Practice Freeway Interchange5-15

Figure 5-13: Freeway On-Ramp with Bike Lane and Exclusive Right-Turn Lane: Added Right-Turn Lane.....5-18

Figure 5-14: Freeway On-Ramp with Bike Lane and Exclusive Right-Turn Lane: Trap Lane-Lane Drop.....5-19

Figure 5-15: Bike-Friendly Retrofit of Freeway On-Ramp5-21

Figure 5-16: Bike-Friendly Retrofit of Freeway Off-Ramp.....5-21

Figure 5-17: Arterial with Acceleration/Deceleration Lane.....5-22

Figure 5-18: Grade-Separated Intersection of Two Highways - Bicycles Permitted5-26

Figure 6-1: Detector Type SA Details.....6-6

Figure 6-2: Detector Layout at Five-Phase Signalized Intersection6-7

Figure 7-1: Bike Lane on Roadways Where Grade is $\geq 5\%$7-2

Figure 7-2a: Bike Lane Width - 30 mph or less Posted Speed7-3

Figure 7-2b: Bike Lane Width - 35-40 mph Posted Speed7-3

Figure 7-2c: Bike Lane Width - 45 mph or more Posted Speed7-3

Figure 7-3: Optimal Bike Lane Pavement Marking Set.....7-5

Figure 7-4: Bike Lane Striping Options with On-street Parking7-5

Figure 7-5: Bike Lane Striping Option at Intersection Approach7-7

Figure 7-6: Bulbout with Bike Lane.....7-8

Figure 7-7: Bulbout without Bike Lane7-9

Figure 7-8: Bike Lane Striping and Detector Layout at Signalized Intersection Approach7-10

Figure 7-9: Loop Detector Pavement Marking7-10

Figure 7-10: Bike Lanes and One-Way Streets.....7-11

Figure 7-11: Contra Flow Bike Lane Options on One-Way Streets7-12

Figure 7-12: Bike Lanes on Bus Routes (Far Side Bus Stop).....7-13

Figure 7-13a: Curbside BRT - Dedicated Lanes with Bike Lanes.....7-14

Figure 7-13b: Median BRT - Dedicated Lanes with Bike Lanes and No Parking.....7-15

Figure 7-13c: Median BRT - Dedicated Lanes with Bike Lanes and Parking7-15

Figure 7-14: Bicycle - Motor Vehicle Conflicts at Conventional Intersections7-16

Figure 7-15: Bicycle - Motor Vehicle Conflicts at Roundabouts7-16

Figure 7-16: Roundabouts with Cycle Tracks7-17

TABLE OF CONTENTS

Figure 7-17:	Bicycle Operating Space in Typical Travel Lane	7-18
Figure 7-18:	Typical Sharrow Pavement Marking Installation	7-20
Figure 7-19:	Wide Shoulders - Bicycle-Friendly Details	7-24
Figure 7-20:	Rural Road Cross Section on Constrained Right of Way	7-25
Figure 7-21:	Rural Road with Shoulders and Bike Path	7-26
Figure 7-22:	Shoulder Rumble Strip Details	7-30
Figure 7-23:	Cycle Track Design Elements	7-33
Figure 8-1:	Bicycle Boulevard Typical Treatment.....	8-5
Figure 8-2:	Barrier Design: Bicycle Boulevard.....	8-6
Figure 8-3:	Forced Right-Turn Channelization.....	8-6
Figure 8-4:	Sinusoidal Speed Hump.....	8-7
Figure 8-5a:	A Typical Cul-de-Sac Standard Detail.....	8-12
Figure 8-5b:	Cul-de-Sac Woonerf Conceptual Layout	8-12
Figure 8-6:	Example of a European Woonerf.....	8-13
Figure 8-7:	Residential Woonerf Retaining Curb, Gutter and Sidewalk	8-14
Figure 8-8:	Typical Parklet Layout.....	8-17
Figure 9-1:	Right of Way Width Allocation for Typical Bike Path (Moderate Pedestrian Volumes).....	9-6
Figure 9-2:	Bike Path Width Allocation in Severely Constrained Right of Way.....	9-7
Figure 9-3:	Traffic Control Options at Trail Intersections.....	9-9
Figure 9-4:	Guidelines for Traffic Control Devices at Trail Intersections	9-9
Figure 9-5:	Typical Bicycle Bridge Cross Section	9-11
Figure 9-6:	Optimal Path Entry Design to Discourage Motor Vehicles	9-14
Figure 9-7:	Preferred Bollard Design - Flexible Post Channelizer.....	9-15
Figure 9-8:	Bollard Design if Flexible Post Not Used.....	9-15
Figure 9-9:	Optimal Bollard Layout and Ramp Design	9-16
Figure 9-10:	Roadside Path with Bicycles Permitted	9-18
Figure 9-11:	Median Bike Path	9-19
Figure 10-1:	Typical Dimensions - Inverted U and Variations.....	10-6
Figure 10-2:	Bike Rack Design Options	10-7
Figure 10-3:	Bike Locker Placement Criteria	10-8
Figure 10-4:	Bike Rack Placement Criteria (In Plazas or Near Buildings).....	10-9
Figure 10-5:	Bike Rack Placement Criteria (Adjacent to Curb).....	10-10
Figure 10-6:	Bike Rack Placement Criteria (On-Street Parking Space).....	10-11

FOREWORD

The VTA Bicycle Technical Guidelines (BTG) reproduce many of the Caltrans Highway Design Manual's (HDM) standards and guidelines as well as those from other manuals. The BTG are intended to supplement and augment these manuals, by providing guidance on when and how to better accommodate the many types of bicyclists; to the extent that the Caltrans standard is a "minimum" dimension or practice, this manual presents best practice options for some situations. The VTA "Best Practices" included herein are not a substitute for professional engineering judgment and may not be appropriate for a specific situation. As with the HDM, the BTG is not a substitute for engineering knowledge, experience, or judgment. Reference to and knowledge of the original design manuals is assumed.

The California Manual of Uniform Traffic Control Devices includes both FHWA's Manual of Uniform Traffic Control Devices (MUTCD) and all policies on traffic control devices issued by the California Department of Transportation (Caltrans). When FHWA issues a revised MUTCD, it is not effective in California until Caltrans and the California Traffic Control Devices Commission (CTCDC) review it and incorporate the changes into the California MUTCD through formal efforts. Therefore it is the California MUTCD (MUTCD-CA) that is the official manual for use in California and the manual used in the Bicycle Technical Guidelines as reference. In the few cases where there is a section that is only in the California MUTCD and not in the federal MUTCD, the citation will be followed by "(CA)", e.g. MUTCD-CA Section 4D.104(CA). Similarly, when a sign or figure is cited in the BTG, the corresponding sign number is followed by "(CA)", e.g. R81 (CA) to denote a sign or figure that only appears in the California MUTCD. In all other cases, the citation refers to the MUTCD number, e.g. R4-4.

Since the Highway Design Manual is the primary manual for bikeway design in California, the purpose of the HDM has been reprinted below and is hereby incorporated.

From the Foreword to the Caltrans Highway Design Manual, 2012

Purpose

This manual was prepared for the California Department of Transportation (Department) by the Division of Design for use on the California State highway system. This manual establishes uniform policies and procedures to carry out the State highway design functions of the Department. It is neither intended as, nor does it establish, a legal standard for these functions.

The standards, procedures, and requirements established and discussed herein are for the information and guidance of the officers and employees of the Department.

Many of the instructions given herein are subject to amendment as conditions and experience warrant. Special situations may call for deviation from policies and procedures, subject to Division of Design approval, or such other approval as may be specifically provided for in the text of this manual.

It is not intended that any standard of conduct or duty toward the public shall be created or imposed by the publication of this manual. Statements as to the duties and responsibilities of any given classification of officer or employees mentioned herein refer solely to duties or responsibilities owed by these in such classification to their superiors. However, in their official contacts, each employee should recognize the necessity for good relations with the public.

Scope

This manual is not a textbook or a substitute for engineering knowledge, experience, or judgment. It includes techniques as well as graphs and tables not ordinarily found in textbooks. These are intended as aids in the quick solutions of field and office problems. Except for new developments, no attempt is made to detail basic engineering techniques; for these, standard textbooks should be used.